

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
30 September 2004 (30.09.2004)

PCT

(10) International Publication Number  
**WO 2004/082444 A1**

(51) International Patent Classification<sup>7</sup>: **A47G 29/12**,  
29/122, 29/124, E05B 41/00, 47/00

(21) International Application Number:  
PCT/AU2004/000319

(22) International Filing Date: 17 March 2004 (17.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003901194 17 March 2003 (17.03.2003) AU

(71) Applicant (for all designated States except US):  
**TELEZYGOLOGY INC** [AU/AU]; Suite 1101, 61  
Lavender Street, Milsons Point, NSW 2061 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **RUDDUCK, Dick-**  
**ory** [AU/AU]; 81 Castle Circuit, Seaforth, NSW 2092  
(AU). **GOLDSPINK, Lachlan, Richard** [AU/AU]; Unit  
2, 4 Bates Avenue, Paddington, NSW 2021 (AU).

(74) Agents: **CHRYSILIOU, Kerry et al.**; Chrysiliou Law,  
15-19 Parraween Street, Cremorne, NSW 2090 (AU).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-  
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,  
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,  
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: CLOSURE FOR A COMPARTMENT



(57) Abstract: The invention provides a closure (106) for a compartment (100) having one or more walls (112, 114, 116 and 118) and an opening (110) defined by at least one of the walls (112, 114, 116 and 118). The closure (106) is associated with at least one fastener located inside the compartment (100). The fastener can hold the closure (106) in a first position (eg. closed) relative to the opening (110). The fastener is adapted to cause the closure (106) to assume a second position (eg. open) relative to the opening (110) upon receipt of a suitable signal. The closure (106) has at least on indicium (108) visible from outside the compartment (110). The indicium (108) is adapted to provide a visual indication of a status of the closure (106) or the compartment (110), such as closure open, closure closed, compartment empty, compartment occupied. Instead of indicium (108) or in addition to it, the closure of the invention can include in the fastener means for communicating to a remote device, a status of the closure or the compartment. The closure and the compartment may form an array with other closures and compartments having similar fasteners. In that event, the fastener in each compartment may be addressable.

## Closure for a Compartment

### Technical Field

This invention relates to a closure for a compartment.

The invention may be suitable for a wide range of compartment closures. Suitable  
5 compartments may be mail boxes (letter boxes) and lockers. The invention is not  
limited to these compartments. However, for convenience of description, the disclosure  
below will focus on mail boxes and lockers. Again for convenience, the description  
below will refer to multiple mail boxes and lockers. It is to be understood that the  
invention is not necessarily limited to this and that the invention may also be useful for  
10 stand alone mail boxers and lockers.

### Background

Arrays of private mail boxes are often made available for hire by postal authorities and  
by private organisations. Such mail boxes are operated by keys. A hirer will normally  
pay a fee for use of a private mail box and will be provided with the key appropriate for  
15 the mail box hired. Hiring fees are normally based on periods of time - for example, six  
months. Mail box keys are often lost by the person hiring the mail box and it is normal  
to require a deposit for the key.

It is an object of this invention, at least in some embodiments, to provide a system in  
which there is no need for a keyed lock for each mail box in an array of mail boxes. It  
20 is a further object of the invention, at least in some embodiments, to dispense with the  
need for a traditional key to each mail box. In some embodiments in the invention, the  
means for gaining access to a mail box can be linked with financial accounting for use  
of the mail box.

An array of mail boxes is commonly installed in other situations, for example, in the  
25 foyer of an office building or in the foyer of a condominium (home unit) building. Once  
again, until now each such mail box has normally required an individual lock and a key

to operate that lock. As in the case with private mail boxes, discussed above, it is an object of this invention, in some embodiments, to eliminate the need for a traditional keyed lock for each mail box. Optionally, this invention can provide means for access to an individual mail box which is the same as or combined with means of access to a  
5 door in the office building or condominium building. That door may be the main door into the building, in the case of a security complex, or the door to the individual office or condominium in the building.

Lockers are provided in arrays, similar to mail boxes. For example, an array of lockers may be provided at an airport or a shopping centre for temporary use. Like mail boxes,  
10 such lockers have normally been "hired" by a user by inserting coins into a mechanism provided on each locker. This will normally permit the user to lock the locker and remove the key. Such lockers require not only the coin-freed mechanism but also individual keyed locks, with appropriate keys. Using an appropriate embodiment of the present invention, it is possible to avoid the need for individual coin-freed mechanisms  
15 of the type described and the need for individual traditional locks and keys for each locker.

In gymnasias and clubs, lockers are often provided for the use of members and visitors. Sometimes these are provided for a set charge and sometimes they are provided free. In either case, until now, each locker has required a keyed lock and a key for that lock.  
20 Using an appropriate embodiment of the present invention, such individual keyed locks and keys can be eliminated.

As will be described below, in some embodiments of the invention it is possible to provide communication from the mailbox or locker and/or indicia indicating a status of the mailbox or locker. As an example of communication, a mailbox incorporating an  
25 embodiment of the invention may be able to communicate to a user whether the mailbox contains mail, whether the mailbox has been opened by an authorised user or whether the mailbox has been tampered with. In an even more sophisticated version, the

mailbox may be able to communicate the type of mail in the box. A locker may be able to communicate similarly, if so desired.

The communication may be to the principal user of the mailbox or to another party, for example, a courier. At present, couriers normally require a written acknowledgment of receipt of a courier delivery. This means that the courier will usually have to enter a building, find an authorised person and have that authorised person acknowledge receipt of the delivery. In some embodiments of the invention, it is possible for the compartment, such as a mailbox, to provide acknowledgment of delivery of an article into the mailbox. Communication can be directly to a party accessing the mailbox or to a remote centre.

As an example of indicia, a mailbox may display various signals, for example, a signal that the mailbox is closed, a signal that the mailbox is open and a signal that the mailbox contains mail. A locker may similarly exhibit a signal that it is open or closed and that it is either empty or contains contents.

#### **Summary of the Invention**

In one aspect, this invention provides a closure for a compartment having one or more walls and an opening defined by at least one of the walls, the closure being associated with at least one fastener located inside the compartment and adapted to hold the closure in a first position relative to the opening, the fastener being adapted to cause the closure to assume a second position relative to the opening upon receipt of a suitable signal, wherein the closure includes at least one indicium visible from outside the compartment and adapted to provide a visual indication of a status of the closure or the compartment.

In a second aspect, the invention provides a closure for a compartment having one or more walls and an opening defined by at least one of the walls, the closure being associated with at least one fastener located inside the compartment and adapted to hold the closure in a first position relative to the opening, the fastener being adapted to cause the closure to assume a second position relative to the opening upon receipt of a suitable

signal, wherein the fastener includes means for communicating to a remote device information relating to the closure, the compartment or contents of the compartment.

In a third aspect, the invention provides a closure for a compartment having one or more walls and an opening defined by at least one of the walls, the closure being associated  
5 with at least one fastener located inside the compartment and adapted to hold the closure in a first position relative to the opening, the fastener being adapted to cause the closure to assume a second position relative to the opening upon receipt of a suitable signal, wherein the compartment forms an array with other compartments having similar fasteners, the first-mentioned fastener is addressable and the signal is provided by  
10 means external to the compartment and capable of addressing the first-mentioned fastener.

The invention includes any combination of the first, second and third aspects of the invention.

Further, the invention provides a compartment having such a closure, as well as an array  
15 of such compartments.

The compartment is preferably a mailbox or locker, but the invention is not limited to these options. In the case of a mailbox, the compartment may have a single opening, being that defined by at least one of the walls. Commonly, a mailbox compartment will be square or rectangular in cross section and the opening will be defined by four of the  
20 walls. A mailbox compartment may be closed by a wall located opposite the opening. Alternately, the mail box compartment may be open at that location. This enables mail workers to have access to the internal end of the compartment, for easy deposit of mail.

When the compartment is a locker this will normally be closed on all sides except for the opening which is closed by the closure of the invention.

25 The compartment is not limited to any particular shape. For example, it may be circular in cross section, in which case the opening may be defined by a single, continuous wall.

The closure should be shaped to adequately close the opening and will normally take the form of the cross-sectional shape of the compartment. However, it is not necessary that the closure completely seals off the compartment. For example, when the compartment is a mail box, a letter slot may be provided at one end of or through the closure. In other cases, it will be desirable that the closure does provide an adequate seal.

The closure is preferably hinged or otherwise attached to the compartment at the opening. Preferably, in the first position the closure closes the opening. It is further preferred that this is the "at rest" position and that no energy is required to maintain this configuration. The nature of the fastener (refer description below) will in many cases determine if the closure is at rest in the closed position.

The second position is preferably the "open" configuration and it is preferred that this is achieved upon the application of energy via the signal.

The fastener may take any appropriate form. While not limiting the nature of the fastener, it is preferred that the fastener is one of those disclosed or to be disclosed by Telezygology Pty Limited or Telezygology Inc in patent specifications. Reference is made to the following patent specifications, the contents of which are hereby imported by reference: International Patent Application No. PCT/AU99/00185, International Patent Application No. PCT/AU03/00759, International Patent Application No. PCT/AU03/00933 and Australian Provisional Patent Application No. 2003901352.

An example of one such fastener includes a fastening element having a flexible beam and an engagement means; and actuating means attached to the fastening element and including a material adapted to contract when activated; the beam being moveable, upon contraction of the material, between an engagement position and a disengagement position. Preferably, the material adapted to contract when activated is chosen from the group; shape memory wire; shape memory strip and shape memory alloy in sputter form.

Such a fastener may be an overhang fastener which includes a shape memory material adapted to assume a first position in which the fastener holds the closure in the first position relative to the opening and a second position in which the fastener causes the closure to assume the second position relative to the opening. In this example, the  
5 shape memory material is activated to assume its second position upon the application of suitable energy provided by the signal.

Shape memory materials are known. Currently, the best known of these is a shape memory alloy, predominantly or wholly made of titanium and nickel, but which may also include other material, such as aluminium, zinc and copper. Such a shape memory  
10 alloy is capable of changing shape at a predetermined transition temperature. Some shape memory alloys adopt one shape below the predetermined transition temperature and change to a second shape once the temperature exceeds the transition temperature. Usually, when a shape memory alloy cools below the transition temperature, it is capable of adopting the first shape again.

15 In the embodiment where the fastener is an overhang fastener, it preferably includes shape memory alloy in the form of a titanium-nickel wire. When sufficient energy in the form of an electrical current is applied, this wire heats to or above a temperature at which the material shrinks by about 4-5 percent. Since the fastener is in the form of an overhang hook, once the material shrinks to the desired extent, the hook can be caused  
20 to bend away from the configuration in which the closure is held in closed relationship to the opening. Once the electrical current ceases, the alloy can cool below the transitional temperature and can assume its original configuration, causing the closure to close the opening.

In the simplest form of this embodiment of the fastener, the signal causes the electric  
25 current to heat the shape memory alloy sufficiently to contract the shape memory material, lifting the hook away from engagement with a shank or a ledge or other suitable part of the closure or compartment. This releases the closure which can be pulled open by hand, especially if the closure is hinged at or toward its top. If the

closure is hinged at or towards its bottom, release by the fastener may permit the closure to fall open under the influence of gravity. In either case, to close the closure, it may be necessary merely to push the closure into the closed position. Assuming that the electrical current has ceased and the shape memory material has elongated to its original  
5 position, the fastener may be designed to "click" back into the locked position when the closure is pressed against the opening.

In a variation of this embodiment of the fastener, it may be desired to maintain the shape memory material in the contracted position for a desired length of time. This can be carried out by using less energy (such as an electrical current) than that required to  
10 change the shape memory material to the contracted configuration in the first place. For example, an insulating tube may be maintained around the shape memory material, the tube comprising or including Teflon or other insulation, for example.

The two variations referred to above may be regarded as monostable. In the case of a monostable fastener, the fastener may take the form of a titanium-nickel wire joined to a  
15 resilient material. When the wire is heated to a sufficient temperature, shrinkage occurs and the resilient material bends to accommodate the shrinkage. When the wire cools below the relevant temperature, it elongates. The bias of the resilient material causes the monostable fastener to resume the original position.

In a further variation of this embodiment of the fastener, the fastener can be bistable. In  
20 this variation, there are two pieces of the titanium-nickel wire in the fastener. Each can be separately activated by an electrical current. When the first wire is activated, it shrinks and distorts the fastener in the desired way. This configuration is designed to lack any bias urging the first wire into the original position when it cools. Consequently, when the first wire cools, the fastener stays in the second position. In  
25 order to restore the fastener to the first position, it is necessary to activate the second wire by the application of suitable heat (for example by electricity), so that it shrinks and draws the fastener back to the first position.



The choice of variation of fastener may depend on the environment and use of the compartment.

The overhang fastener in this embodiment, regardless of the variation selected, may be a discrete overhang fastener or a linearly extended overhang fastener. In the case of the discrete overhang fastener, terminals in the base of the fastener may be used to connect to a electrical supply. In the case of the linear form of overhang fastener, one or more buses may be incorporated in the fastener in order to transmit electrical energy throughout the length of the liner overhang fastener. A metal wire lashing may connect one bus to another along the length of the fastener. The lashing may be integrated with the fastener.

As an another example, the fastener may be a fastener assembly for releaseably securing an element, the element including a post having a groove, the assembly including a bar adapted to engage the groove to secure the element, the assembly also including a connecting means attached to the bar and consisting of or including shape memory material which, upon application of suitable energy, is adapted to change shape and draw the bar out of engagement with the groove, thus releasing the element.

Preferably, the element has more than one post, each having a groove. The bar may engage the groove in more than post. Preferably, the bar engages the groove in each of two posts.

Regardless of the type of fastener selected, there may be one or more fasteners per compartment. In the case of a fastener such as the discrete overhang fastener described above, preferably at least two fasteners are used, for security reasons. If the linearly extended overhang fastener referred to above is used, only one fastener may be preferred, depending on the length of the fastener.

Each fastener is preferably located on the closure, but may instead be located on a wall of the compartment, for example.

When there is more than one fastener associated with a closure, only one fastener need be addressable in relation to the third aspect of the invention. The other fastener or fasteners may be "slave" fasteners.

Fasteners may be encrypted for added security.

- 5 In relation to the first aspect of the present invention, the closure includes at least one indicium visible from outside the compartment and adapted to provide a visual indication of a status of the closure or the compartment. The indicium may show whether the compartment has a closed or an open status. It may show whether there is anything in the compartment. For example, when the compartment is a mail box, the  
10 indicium may show whether there is mail in the mail box. When the compartment is a locker, the indicium may show whether there are any clothes or other contents in the compartment.

The indicium may take the form of light emitting diode (LED) chips. For example, the indicium may comprise a red, a green and a blue LED set into the closure panel so as to  
15 be capable of emitting an appropriate coloured light visible from outside the compartment. The LEDs are preferably linked to the fastener. When the fastener is holding the closure in the first position, for example, the closed position, there may be no light or the green LED may be lit. When the fastener has caused the closure to assume the second position, for example, open so as to expose the opening, the red LED  
20 may be lit. If the fastener is capable of sensing contents of the compartment and senses that the compartment is not empty, the blue LED may be lit. Thus, an external inspection of the compartment can readily indicate status. When the green light shows, the user knows that the compartment is safely closed. When the red light shows, the user is warned that it is open and is alerted to inadvertently leaving the compartment  
25 unlocked. When the blue light shows, the user is prompted to open the compartment to take out mail or contents if the user so desires. In this aspect, the indicium is not necessarily linked to the fastener; other arrangement are within the scope of this invention. Any suitable sensing mechanism may be used.

In the second aspect of the invention, the fastener includes means for communicating to a remote device information about the closure, the compartment or its contents. Such a remote device is preferably a computer (via email) or a mobile phone (via a text message). The invention is not limited to these possibilities and communication may  
5 take place by other means and in other forms, such as audible signals, for example.

The communication may take any desirable form. For example, in the case of a mail box, the communication may indicate that mail has been received in the mail box. If the mail carries a particular coding readable by the fastener, such as a radio frequency identification tag or a bar code, the communication may include the type of mail, and/or  
10 the identity of the sender. For example, the communication may differentiate between bills and checks. The communication can be useful to prompt the user to visit the mail box and extract mail. This can avoid the need for unnecessary visits to a mail box, only to find that the mail box is empty.

When the compartment is a locker or a mail box, the communication may be to the  
15 effect that the compartment has been tampered with. The communication can enable the user to take swift action to apprehend the person attempting or achieving unauthorised access to the compartment or, at worst, to promptly repair the closure to the compartment.

The communication may be to the effect that the contents of the compartment are  
20 dangerous, for example, explosives. The indicium (refer above) may also indicate this, for example, by pulsing a red signal.

The communication may comprise or include a acknowledgment of deposit of an article in the compartment. For example, the article may be a letter or package carrying a radio frequency identification tag or a bar code, for instance. The identifying indicia may be  
25 readable inside the compartment and convey confirmation of receipt to, for example, a central computer run by a courier company, or to a hand-held device of the courier. As another example, the identifying indicia may be read at the time of deposit by swiping it

past a reader associated with the compartment and this may be independent of the fastener. Appropriate readers are known and will be apparent to one skilled in the art.

Preferably, the communication means forms part of the fastener. However, the invention is not necessarily limited to this embodiment.

- 5 Communication may take place in any suitable manner and by any suitable means.

Set out below are non-limiting examples of methods which may be suitable for communication to the fastener for access control activation. It will be appreciated by one skilled in the art that many of these methods are also suitable for communication to the remote device as to, for example, information regarding the closure, the  
10 compartment or its contents.

Communication may take place by a wireless link from a hand-held terminal to the fastener, for example by a custom radio link, by "Bluetooth", by "Zigbee", by "WiFi (802.11)", by inductive coupling, by infrared, microwave or visible light, or by sound energy, such as ultra sound.

- 15 Communication may take place by wireless link from a hand-held device to an external system which then controls the fastener, for example by GPS (sms/mms), GPRS, WiFi to Internet access point, custom radio link, email or voice call to operator. Communication from the external system to the compartment may be via dial-up connection, broad band Internet, GPS, GPRS, Wifi and so on.

- 20 As other examples, communication may take place from a push button keyfob, using radio frequency communication, in a similar manner to a garage door opener or a car alarm keyfob. Another example is the entry of a code using a keypad. Communication can take place by a contact-type or contactless smart card. A magnetic strip card swipe may be used, or an optically coded card or device, for example carrying a bar code or  
25 coded perforations, etc. Communication can take place using an ID chip, similar to a microchip used on animals, being magnetically or radio frequency coupled. Biometric

methods may be used, such as fingerprint scan, retina scan, optical image recognition, voice recognition, DNA scan. An RFID scan may also be used.

These examples of suitable communication can be applied to any appropriate aspect of the invention.

- 5 In the third aspect of the invention, one particular fastener is addressable via a signal provided by means external to the compartment and capable of addressing the fastener, in an array of compartments. The means external to the compartment preferably involve a smart card and a smart card reader. An authorised user of the compartment (such as a mail box or locker) is provided with an encoded smart card. When this is passed in  
10 front of an appropriate reader, or inserted in it, the reader checks the authorisation encoded in the card and addresses the appropriate fastener, providing a signal to the fastener to cause the closure to assume the second position relative to the opening (eg, to open the compartment). It will be appreciated that an array of compartments may require merely a single reader, thus saving the considerable costs of individual locks and  
15 keys to each compartment. Further, if a suitable fastener is addressable in this aspect it may be necessary to use only a single electrical wire connecting all of the fasteners in series, representing a further cost saving. It is possible to supply both power and data to each addressable fastener, which can include an embedded switch and processor. The fasteners can be addressed on an individual basis or as part of a group.
- 20 The closure of the invention can be used to log usage of the compartment, for example, via an intelligent fastener.

### **Summary of the Drawings**

The invention will now be described in connection with certain non-limiting examples described in the attached drawings. In the drawings:

- 25 Figure 1 shows in side view a simple form of a first embodiment of a fastener useful in association with the closure of the invention, in fixed configuration;

Figure 2 shows the fastener of Figure 1 in the released configuration;

Figure 3 shows the embodiment of Figure 1 in rear view;

Figure 4 shows a second embodiment of a fastener in linear form;

Figure 5 is a side view of a third embodiment of a fastener;

5 Figure 6 is an enlarged form of the embodiment in Figure 5;

Figure 7 is a rear view of the embodiment of Figure 6;

Figure 8 is a front view of the embodiment of Figure 6;

Figure 9 is a top view of the embodiment of Figure 6;

Figure 10 is a sectional view along the lines A-A of Figure 8;

10 Figure 11 is a sectional view along the lines B-B of Figure 8;

Figure 12 shows in reduced form the embodiment of Figures 13-18;

Figure 13 is a side view of the embodiment of Figure 12, designed for "intelligent" use;

Figure 14 is a top view of the embodiment in Figure 12;

15 Figure 15 is a bottom view of the embodiment in Figure 12;

Figure 16 is a front view of the embodiment of Figure 12;

Figure 17 is a sectional view taken along the lines A-A of Figure 16;

Figure 18 is a sectional view taken along the lines B-B of Figure 16;

20 Figure 19 shows an embodiment of an array of mail boxes capable of being operated by use of a smart card;

Figure 20 shows the mail boxes of Figure 19 with one of the mail boxes indicating visually a status of the closure and also illustrating communication with two remote devices; and

Figure 21 is a similar view to that in Figure 20 but illustrating a visual indication of different status and a different communication to those in Figure 20.

### **Detailed Description of the Drawings**

Referring first to Figures 1 to 3, the fastener indicated generally at 10 is principally made of suitable deformable material in shank 12 and hook 14. Titanium/nickel shaped memory wire 16 connects the top of hook 14 with base 18. Base 18 is shown mounted in an appropriate recess 20 retaining fastener 10 in position. Base 18 has terminals 22 and 24 connected to an electric power supply (not shown). Wire 14 may be suitably insulated to improve performance (insulation not shown).

Fastener 10 takes the form of an overhang clip which, in Figure 1, is shown in the first position engaging clip 26 being formed integrally with element 28, base 18 of overhang clip 10 being restrained by the shape of recess 20 in another element 30.

In Figure 2, wire 16 has been heated by the application of power via terminals 22 and 24 in base 18. Wire 16 has contracted, causing hook 14 to be drawn away from contact with hook 26. The separation between hook 14 and hook 26 is somewhat exaggerated in Figure 2 for convenience of illustration. If wire 16 is permitted to cool, for example by suitable reduction in power being applied via terminals 22 and 24, overhang hook 10 can return to the state shown in Figure 1 and re-engage hook 26.

Turning now to Figure 4, parts which are similar to those in Figures 1 to 3 carry the same numerals. In this embodiment, linear overhang hook 40 has shank 12, hook 14 and base 18. Shape memory wire (not shown) is integrated with overhang hook 40. Also included are positive and negative buses 42 and 44, connecting by metal wire lashing 46. Overhang hook 40 is especially suitable for providing a continuous form of fastener

Turning now to the embodiment in Figures 5 to 11, once again, the same numerals will be used for similar parts as in the embodiment in Figures 1 to 3. Except for base 32, overhang fastener 50 is very similar to that in Figures 1 to 3. No shape memory wire is shown in the embodiment in Figures 5 to 11 but of course it is included. As may be  
5 seen from Figures 9 and 10, vertical holes 34 are included in base 32. Base 32 also includes horizontal cavity 36. The purpose of holes 34 and cavity 36 is to accommodate screws.

With reference now to Figures 12 to 18, overhang fastener 60 has shank 12 and hook 14, similarly to previous embodiments. However, base 62, which contains cut outs 64  
10 either side of bridge 66 (refer Figure 15) includes cavity 68 designed to receive a microprocessor or connect to a circuit board so that fastener 60 can be "addressable". A reduced scale version of fastener 60 is shown in Figure 12.

Turning now to Figure 19, this shows a number of mail boxes 100 set out in a rectangular array. Each mail box 100 has a letter slot 102 and an area 104 on closure  
15 106 for insertion of detail such as the number of the box or the name of the owner, etc. Closure 106 also includes LED 108 for indicating status of closure 106 or the compartment within. The compartment has an opening 110, of which letter slot 102 forms part. Opening 110 is defined by compartment walls 112, 114, 116 and 118. The compartment may also be defined by a rear wall (not visible in Figure 19).

20 Card reader 120 is mounted on side wall 122 of the array of mail boxes 100. When a user 126 passes smart card 124 in front of card reader 120, card reader 120 reads information stored on smart card 124 and, if appropriate, addresses the fastener or fasteners (not shown) in the appropriate mail box. In this embodiment, it will be assumed that the appropriate mail box is 100A. Card reader 120 then causes an  
25 electrical current to be passed through a multi-drop communications and power feed bus connecting all the mail boxes 100. The fastener or fasteners on mail box 100A are addressed, sufficient current is applied to cause shape memory alloy in the fastener or fasteners to contract causing the fastener or fasteners to release and closure 106 to open.



LED 108 may be unlit to show that closure 106 is properly closing opening 110 on mail box 100. Alternately, LED 108 may be assigned a particular colour, such as green, when in this situation. In the case of mail box 100A, once the fastener has caused the closure to open, LED 108, connected to the fastener or fasteners, may emit a red colour  
5 to indicate that the status of mail box 100A is "open".

It should also be mentioned that LED 108 may emit a different colour, such as blue, to indicate that there is mail within mail box 100.

Smart card 124 is shown having an endorsement 128 as to a particular amount of currency. If the array of mail boxes 100 represents private mail boxes operated by a  
10 private enterprise for profit, a user may be assigned a particular mail box 100 (such as mail box 100A) and be given smart card 124 upon payment of the appropriate fee (in this case, \$25.00). Smart card 124 may be programmed to expire after a particular period or once a particular date is reached. Alternately, smart card 124 may be configured so that a small fee is deducted from smart card 124 each time it is read by  
15 card reader 120. The fee may be deducted against a credit on smart card 124 or from an authorised bank account. More frequent operation of mail box 100A will use up the credit on smart card 124 more quickly. If LED 108 shows whether the compartment in mail box 100A is empty or not, unnecessary opening of mail box 100A is eliminated, thus maximising the value to be obtained from smart card 124.

20 Smart card 124 may have multiple uses. For example, it may be programmed to open the door of a condominium, or it may also operate as a credit card.

With reference now to Figure 20, where the same numerals as in Figure 19 are used for the same parts, mail box 100B is shown with crowbar 130 inserted so as to force open closure 106. LED 108 is emitting a chosen colour, such as red, to indicate that  
25 tampering has taken place or merely that closure 106 is in the open status. At the same time, a message has been transmitted to either or both computer 132 and mobile phone 134. The signal can be sent from mail box 100B using known technology. It may be received on computer 132 via email and on mobile phone 134 via a text message. In the

case of computer 132, the email is shown in display 136. In the case of mobile phone 134, the text message is shown in display 138.

In Figure 21, the same numerals are used as in the case of Figures 19 and 20. In Figure 21, mail 140 is inserted in letter slot 102, a fastener (not shown) within mail box 100B  
5 or some other means senses the presence of mail 140 and causes LED 108 to emit a chosen colour, such as blue. At the same time, LED 108 transmits a message by email to computer 132 or by a text message to mobile phone 134. Computer 132 displays the message that mail has been received on display 136. Mobile phone 134 displays a similar message on display 138.

- 10 If mail 140 carries a suitable readable tag, such as a radio frequency identification tag the nature of that mail may be messaged to computer 132 and/or mobile phone 134, as appropriate. Computer 132 may of course be a hand-held computer carried by a courier, so that the courier can receive acknowledgment of the delivery of the mail.

#### **Industrial Applicability**

- 15 The invention in its various aspects can greatly improve efficiency and lower costs in relation to compartments, especially mail boxes and lockers. The invention can save unnecessary labour, it can save time and it can enable economic benefits in the operation of commercial mail boxes and lockers.

It will be apparent that many other versions of the invention may be devised and are  
20 within the scope of this disclosure, without departing from the spirit and scope of the invention.

**Claims**

1. A closure for a compartment having one or more walls and an opening defined by at least one of the walls, the closure being associated with at least one fastener located inside the compartment and adapted to hold the closure in a first position  
5 relative to the opening, the fastener being adapted to cause the closure to assume a second position relative to the opening upon receipt of a suitable signal, wherein the closure includes at least one indicium visible from outside the compartment and adapted to provide a visual indication of a status of the closure or the compartment.
- 10 2. A closure for a compartment having one or more walls and an opening defined by at least one of the walls, the closure being associated with at least one fastener located inside the compartment and adapted to hold the closure in a first position relative to the opening, the fastener being adapted to cause the closure to assume a second position relative to the opening upon receipt of a suitable signal,  
15 wherein the fastener includes means for communicating to a remote device information relating to the closure, the compartment or contents of the compartment.
3. A closure for a compartment having one or more walls and an opening defined by at least one of the walls, the closure being associated with at least one fastener  
20 located inside the compartment and adapted to hold the closure in a first position relative to the opening, the fastener being adapted to cause the closure to assume a second position relative to the opening upon receipt of a suitable signal, wherein the compartment forms an array with other compartments having similar fasteners, the first-mentioned fastener is addressable and the signal is provided  
25 by means external to the compartment and capable of addressing the first-mentioned fastener.
4. A closure for a compartment having one or more walls and an opening defined by at least one of the walls, the closure being associated with at least one fastener

located inside the compartment and adapted to hold the closure in a first position relative to the opening, the fastener being adapted to cause the closure to assume a second position relative to the opening upon receipt of a suitable signal, wherein the closure includes at least one indicium visible from outside the compartment and adapted to provide a visual indication of a status of the closure or the compartment, and wherein the fastener includes means for communicating to a remote device information relating to the closure, the compartment or its contents.

5. The closure of any one of claims 1, 2 or 4, wherein the compartment forms an array with other compartments having similar fasteners, the first-mentioned fastener is addressable and the signal is provided by means external to the compartment and capable of addressing the first-mentioned fastener.
6. The closure of any one of claims 1-5, wherein the compartment is a mail box or locker.
7. The closure of claim 6, wherein the compartment is a mail box having an internal opening for deposit of mail.
8. The closure of any one of claims 1-7, having a slot provided at one end of or through the closure.
9. The closure of any one of claims 1-8, wherein the closure is hinged to the compartment at the opening.
10. The closure of any one of claims 1-9, wherein in the first position the closure closes the opening.
11. The closure of claim 10, wherein the fastener located inside the compartment is adapted to hold the closure in the first position relative to the opening without input of energy.

12. The closure of any one of claims 1-11, wherein in the second position the closure permits access to the opening upon receipt of the signal.
13. The closure of any one of claims 1-12, wherein the fastener includes a fastening element having a flexible beam and an engagement means; and actuating means  
5 attached to the fastener and including a material adapted to contract when activated; the beam being moveable, upon contraction of the material, between an engagement position and a disengagement position.
14. The closure of the claim 13, wherein the material adapted to contract when activated is chosen from the group; shape memory wire, shape memory strip and  
10 shape memory alloy in sputter form.
15. The closure of claim 13 or 14, which includes two of the actuating means attached to the fastening element.
16. The closure of claim 15, wherein one of the actuating means is adapted to cause the beam to move to the disengagement position and the other actuating means is  
15 adapted to cause the beam to move to the engagement position.
17. The closure of any one of claims 1-12, wherein the fastener is a fastener assembly for releasably securing an element, the element including a post having a groove, the assembly including a bar adapted to engage the groove to secure the element, the assembly also including a connecting means attached to the bar and  
20 consisting of or including shape memory material which, upon application of suitable energy, is adapted to change shape and draw the bar out of engagement with the groove thus releasing the element.
18. The closure of claim 17, wherein the element has more than one post, each having a groove.
- 25 19. The closure of claim 19, wherein the bar is adapted to engage the groove in more than one post.

20. The closure of any one of claims 17-19, wherein the shape memory material is a titanium-nickel wire and the suitable energy is heat.
21. The closure of any one of claims 1-20, wherein the fastener is adapted to cause the closure to assume the second position relative to the opening by releasing the closure, the closure adapted to fall open under the influence of gravity.
22. The closure of any one of claims 1-21, wherein the closure is adapted to return to the first position from the second position by the application of pressure of the closure against the opening.
23. The closure of any one of claims 1-22, the closure being associated with two or more fasteners.
24. The closure of any one of claims 1-23, wherein each fastener is located on the closure.
25. The closure of any one of claims 1-23, wherein each fastener is located on a wall of the compartment.
26. The closure of claim 3, where there is more than one fastener associated with the closure, but only one fastener is addressable.
27. The closure of claim 3 or 26, wherein at least one fastener is encrypted.
28. The closure of claim 1, wherein the indicium shows one or more of the following:
- (i) whether the closure is in the first position or the second position;
  - (ii) whether the compartment contains contents or is empty.
29. The closure of claim 1 or 28, wherein the indicium takes a form of one or more light emitting diode chips.

30. The closure of claim 29, wherein the fastener is linked to the light emitting diode chip or chips.
31. The closure as claimed in claim 2, wherein the fastener is adapted to read information on an article located inside the compartment and to communicate  
5 information regarding the article to the remote device.
32. The closure as claimed in claim 1 or 31, wherein the remote device is a computer and the means for communicating is adapted to communicate by email to the computer.
33. The closure as claimed in claim 1 or claim 31, wherein the remote device is a  
10 mobile phone and the means for communicating is adapted to communicate a text message to the mobile phone.
34. The closure of claim 2, wherein the information relates to status of the closure and is chosen from the group being closure open, closure closed and closure damaged.
- 15 35. The closure of claim 2, wherein the information relates to status of the compartment and is chosen from the group: compartment empty, compartment occupied, compartment occupied by dangerous contents.
36. A compartment having the closure of any one of claims 1-35.
37. The compartment of claim 36, when associated with means for reading  
20 identifying indicia to be placed within the compartment.
38. An array of compartments as claimed in claim 36 or 37.
39. The array of claim 38, linked to a smart card reader.
40. The array of claim 38 or 39, wherein the fasteners are connected in series.

41. The array of any one of claims 38 to 40, wherein each fastener is addressable on an individual basis or as part of a group.
42. The array of claim 38, wherein the smart card reader is configured to deduct a fee each time a smart card is read by the smart card reader.
- 5 43. The array of claim 42, wherein the fee is deducted against a credit on the smart card or from a remote account.
44. The array of claim 42 or 43, wherein the smart card is adapted to open another closure and/or to operate as a credit card.
45. A closure substantially as herein described with reference to figures 1, 2 and 3 or  
10 4 or figures 5-11 or figures 12-18 or figure 20 or figure 21.
46. An array of compartments substantially as herein described with reference to figure 19.






Figure 1

Figure 2

Figure 3




Figure 4

Figure 5






Figure 9



TOP VIEW

Figure 11



FRONT VIEW

LEFT VIEW

REAR VIEW

SECTION A-A  
SECTION B-B

Figure 6

Figure 7

Figure 8

Figure 10




Figure 14






Figure 13



SECTION A-A

Figure 17



SECTION B-B

Figure 18

SIDE VIEW

FRONT VIEW




Figure 15

BOTTOM VIEW




Figure 12




Figure 19





Figure 20



# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/AU2004/000319

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> Int. Cl. <sup>7</sup> : A47G 29/12, 29/122, 29/124, E05B 41/00, 47/00. According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) IPC: A47G 29/12, 29/122, 29/124, E05B 41/00, 47/00, E05G 1/02, 1/10. Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched AU IPC: A47G 29/12, 29/122, 29/124, E05B 41/00, 47/00, E05G 1/02, 1/10. Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) DWPI: IPC: A47G 29/12, 29/122, 29/124, E05B 41/00, 47/00, E05G 1/02, 1/10 and (lock+,closure+,fasten+) and (signal+,communicat+,indicat+,) and (bank+,array+,multiple compart+,letterbox+,mailbox+,locker+)		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	Derwent Abstract Accession No.99-161199/14, Class P27, JP 11018916 A (MATSUSHITA DENKI SANGYO KK) 26 January 1999. See entire abstract.	1 to 12.
Y	Derwent Abstract Accession No.2002-275238/32, Class P25, JP 2002017554 A (FULLTIME SYSTEMS KK) 22 January 1999. See entire abstract.	1,2,4.
Y	Derwent Abstract Accession No.96-237022/24, Class Q47, JP 08093287 A (MIWA LOCK CO LTD) 9 April 1996. See entire abstract.	1,2,3,4.
Y	Derwent Abstract Accession No.98-575967/49, Class T01, JP 10257960 A (TOPY KOGYO KK) 29 September 1998. See entire abstract.	1,2,4.
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 2 June 2004		Date of mailing of the international search report 9 JUN 2004
Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaaustralia.gov.au Facsimile No. (02) 6285 3929		Authorized officer  <b>R. WEBER</b> Telephone No : (02) 6283 2546

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU2004/000319

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	Derwent Abstract Accession No.96-112094/12, Class Q34, JP 08011984 A (MITSUBISHI DENKI BUIL TECHNO SERVICE KK) 16 January 1996. See entire abstract.	1,2,4.
X	Derwent Abstract Accession No. 2002-298826/34, Class P27, JP 2002034772 A (MATSUSHITA ELECTRIC WORKS LTD) 5 February 2002. See entire abstract.	1 to 12.
X	Derwent Abstract Accession No.98-083737/08, Class W05, JP 09317278 A (ALPHA KK) 9 December 1997. See entire abstract.	3
Y	Derwent Abstract Accession No.2001-632927/73, Class W05, JP 2001243575 A (FULLTIME SYSTEMS KK) 7 September 2001. See entire abstract.	34
X	WO 1997/41542 A (PORTER) 6 November 1997. See entire specification.	1,2,4 to 12.
X	FR 2687298 A (BONIFACE) 20 August 1993. See entire specification.	1,2,4 to 12.
X	FR 2563987 A (SOCIETE DE DISTRIBUTION DE LA BRASSERIE DE LILLE SA.) 15 November 1985. See entire specification.	1,2,4 to 12.
X	EP 389313 B (MORS) 26 September 1990. See entire specification.	3
X	CA 2098973 A (CANADA POST CORPORATION) 23 December 1994. See entire specification.	1 to 12.



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU2004/000319

### Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:  
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a)

### Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

Claims 1, 2 and 4 are directed to a claim for a compartment which can send information of either the status of the closure or its contents, whereas claim 3 is directed to a closure for a compartment in a bank of compartments.

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

#### Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International application No.

**PCT/AU2004/000319**

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
WO	199741542	AU	28234/97	CA	2264296	EP	920686
		US	5774053				
FR	2687298	NIL					
FR	2563987	NIL					
EP	389313	CA	2010365	FR	2644916	JP	2291092
		PT	93293	US	5231272		
CA	2098973	US	5475378				
Due to data integration issues this family listing may not include 10 digit Australian applications filed since May 2001.							
END OF ANNEX							